

# SUBLIMATION PRINTER

热升华打印机

Dual / Three Heads  
2/3 喷头

High Speed  
速度快

Super Reliable  
超稳定

Long Running  
不间断打印



# Sublimation Printer | WJ-740S & WJ-I260S

## • Features



### Epson PrecisionCore Printhead

Equipped with Epson i3200 printhead, powered by Epson PrecisionCore technology. Born for fast speed and long-term running.




### Heating And Drying System

Front & middle & rear heating system + front drying fan + infrared heater are standard equipped to help dry the printed material fast.



### Anti-Collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.



### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes



### Branded Parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.

- ★ New look has heavier, larger structure, and wider printing platform
- ★ Aluminous carriage girder ensures high accuracy of carriage movement
- ★ Dual feeding bar for loading heavy media
- ★ Integrated temperature controller



## • Specification

Model No.		WJ-740S	WJ-1260S
Printhead		2/3 Epson i3200	2/3 Epson i3200
Resolution		2400 dpi max	2400 dpi max
Media	Size	1.8 meter	3.2 meter
	Types	Heat transfer paper	
Speed	Printing Mode	2 Print heads	
	Draft	42 m <sup>2</sup> /h	46 m <sup>2</sup> /h
	Production	32 m <sup>2</sup> /h	34 m <sup>2</sup> /h
	Quality	24 m <sup>2</sup> /h	26 m <sup>2</sup> /h
Ink	Color	CMYK	
	Type	Sublimation Ink	
Cleaning		Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Heating System		Pre / Middle / Post heating syste & IR heater	
Drying System		Equipped	
Feeding & Take up		Standard Equipped	
Rip Software		MainTop (Standard) / FlexiPRINT (Optional)	
Interface		USB 3.0	
Power		AC 110/ 220V, 50/ 60Hz, 2700W	AC 110/ 220V, 50/ 60Hz, 4000W
Size & Weight	Machine	L3130×W710×H1380 mm / 280KG	L4530×W710×H1395 mm / 500KG
	Packing	L3210×W1000×H740 mm / 400KG	L4610×W1000×H740 mm / 640KG

Specifications are subject to change without notice.